



BESLER
GLASS FIBER

TPP
Chopped Strands for
PP Reinforcement



PRODUCT FEATURES

- Boron-free ECR-glass
- Environment friendly
- Excellent mechanical properties
- Low discoloration performance
- Optimal strand integrity
- Improved flow
- Low fuzz
- Improved bulk density for less storage and handling costs

PRODUCT SPECIFICATION

• Glass Type	ECR (B-Free)
• Filament Diameter (μ)	Nom. 13
• Moisture Content (%)	Max. 0.07
• Sizing Type	Silane
• Loss of Ignition (%)	0,65 $\pm$ 0,15
• Compatability	Polypropylene - PPRC
• Fibre Length (mm)	Nom. 4.5 - 6

PACKAGING

Type	Pallet Dimensions (cm)	Pallet Height (cm)	Quantity Per Pallet	Net Weight Per Pallet (kg)
Big bag	114 x 114	150	1	1000 - 1100

STORAGE

Products should be stored in original package in dry and dust free area.
Storage temperature is between 10°C - 30°C at humidity between 50% - 75%. Pallets must be single stacked.

GUARANTEE

All physical & chemical properties represent average values and subject to normal production variations.
The specifications are also subject to change. For current information please contact Beşler Office.



BEŞLER TEKSTİL SANAYİ ve TİC. A.Ş.

Address: Sultansazı Mh. 10. Cd. No:1 O.S.B. İncesu / Kayseri / TÜRKİYE M: +90 (535) 545 18 93 T: +90 (352) 504 06 02 (pbx)

www.beslerglassfiber.com.tr